



Varmtvannsvasker

Dimensions

Length(mm).....	2370	Width(mm).....	980	Height(mm).....	1550
Weight (kg).....	2500				
Lifting/ Transportation.....	Frame with forklift channels and lifting slings. DNV-ST-E271				
Certificate(s) / Serial No:.....	SU-85				

Construction year

Built.....: 2020

Area of use / certification

Onshore/offshore.....: Offshore
Standard.....: II 2 G Ex IIB T4 Gb, Norsok Z-015, Zone 1

Technical information

Feed water tank volume (ltr).....	500		
Jetting-lances (Qty).....	2		
Q-max (l/min).....	18		
P-max (bar).....	270 @ 50Hz	P-max (PSI).....	3916
Max temp. (GrC).....	65		

Connections

Inlet connection.....: 1" Offshore claw coupling
Outlet connection.....: 2 ea. Flushing lance x 25m

Filter

Inlet filter element (type).....: M23R20A +Strainer, 93719-16 i tanken

Pump(s)

Pump1 (type).....: Hawk ATEX XLT1 pump
Pump2 (type).....: Hawk ATEX XLT1 pump

Motor / Engine(s)

Motor1 (type).....: Bartec Varnost 4KTC 160M4 II2G EEx de IIc T4. PTB 99 ATEX 1138
Motor1 (Cert. No.).....: 1462
Motor2 (type).....: Bartec Varnost 4KTC 160M4 II2G EEx de IIc T4. PTB 99 ATEX 1138
Motor2 (Cert. No.).....: 1464

Power supply

Fuse (qty).....	1	Fuse (A).....	125		
EI.Power1.....	400 VD	(Hz).....	50	(kW).....	11,0 (A).....: 22,7
EI.Power2.....	690 VY	(Hz).....	50	(kW).....	11,0
EI.Power3.....	400 VD	(Hz).....	60	(kW).....	11,0
EI.Power4.....	440-480 VD	(Hz).....	60	(kW).....	12,5
EI.Power5.....	660-690 VY	(Hz).....	60	(kW).....	11,0 (A).....: 12,4
Heater.....	2ea Cetal Eexd IIC T5 Type: TPAEL (cert. no. 01 ATEX 6039 X IP 67)				
Starter.....	MES Type 20-007 II 2 (1) G Ex db eb [ia Ga] IIC T4 Gb. Snr 1900864001 Presafe 20 ATEX 58214 X				