



HOSE NITROGEN

Dimensions

Length (mtr).....	10.0
Transport weight (kg).....	14
Weight per mtr (kg).....	1.35
Dimension (inch).....	0.75
OD (mm).....	28.8
ID (mm).....	18.8

Type

Qty. available in stock.....	1097
Fabricator.....	Spir Star
Model.....	Hose Type 20/4
IKM Part number.....	NTS0810M-650B
Suitable for.....	Nitrogen / Gas
Innercore.....	Polyamide (PA)
Steelcords.....	4 layers of high-tensile steel wire

Technical Specifications

Work pressure (bar).....	1040
Work pressure (psi).....	15080
Min. Temperarture (GrC).....	-30
Max. Temperature (GrC).....	60
Bend radius (mm).....	250
End couplings/fittings.....	M36

Additional information

Equipment / Functions.....	WHEN USED WITH NITROGEN GAS: Max working pressure 625 bar
	Outer cover: Polyamide (PA)
	Waterblast: Heat exchanger tube cleaning, surface preparation (concrete removal, surface cleaning of buildings, paint removal), tank and vessel cleaning, ultra high-pressure waterjet cutting and hydro demolition (cutting and demolition of armoured concrete, pipelines, paper or steel)
	Hydraulics: Pressure test equipment (valves, tooling and control panels), hydraulic tools (instrumentation packages for gauges, control of service equipment, hydraulic jacks, hydraulic tools)
	Oil and Gas: Chemical injection, nitrogen service, Gaseous media handling