



IKM Testing AS

Unit Nr. SU-11

VARMTVANNSSVASKER

Offshore

Eexde IIB T4 Sone 1

Iht. Norsok Z-015

Ramme, slings og sjakler iht. DNV 2.7-1



Dimensjon	:	L 900 mm	B 2150 mm	H 1600 mm
Vekt	:	1200 kg		
Løfting/Transport	:	Ramme med trucklommer og løfteskrev.		
Ref. sert./Ser. nr.	:	SU-11		

Tankvolum	:	380 l
Q maks. 60 Hz	:	21 l/min.
Q maks. 50 Hz	:	17 l/min.
P maks. 60 Hz	:	300 bar
P maks. 50 Hz	:	270 bar
Maks. vann temperatur	:	70°C
Tilkopling inn	:	1" Offshore klokopling
Anbefalt forankoplet sikring	:	63 A
Spenningsområde	:	400V / 50Hz og 400-480V / 60Hz

Pumpe	:	Hawk stempelpumpe HC930A	Ser. Nr: 004981
Motor	:	Teve Varnost 3KTC 160L-4 Eexde IIB T3 IP-55	Ser. Nr: 427
	:	380-415 VD 22,0 A 50 Hz	11,0 Kw
	:	660-720 VY 12,8 A 50 Hz	11,0 Kw
	:	400 VD 22,0 A 60 Hz	11,0 Kw
	:	440-480 VD 19,6 A 60 Hz	12,9 Kw
	:	600-690 VY 12,8 A 60 Hz	11,0 Kw
Varmekolber	:	2 stk. Cetal Eexd IIC T6	
	:	400 VD 20,2 A 50-60 Hz	14,0 Kw
	:	440 VD 22,3 A 50-60 Hz	17,0 Kw
	:	480 VD 24,3 A 50-60 Hz	20,2 Kw
	:	660 VY 19,3 A 50-60 Hz	12,7 Kw
	:	690 VY 11,8 A 50-60 Hz	14,0 Kw
Nivåbryter	:	Mobrey Eexd IIC T6 440 V	
Startskap	:	Stahl Cubex 8264/-22-3110	Ser. nr: 308264-1
	:	IIG EEx de IIB T5	
	:	400-480 V Maks last: 72 A 50-60 Hz	
Vannfilter element	:	MP Filtri	
	:	STR0704SG1M90BSP 421488	
Andre opplysninger	:	Levert med 25 m 3/8" slange og spylelanse, mannløkk i tank.	
Bygge år	:	1998, nytt Exde skap i 2008	