



IKM Testing AS

Unit Nr. SU-25

VARMTVANN SVASKER



Offshore

Eexde IIB T4 Sone 1

Iht. Norsok Z-015

Ramme, slings og sjakler iht. DNV 2.7-1

Dimensjon	:	L 1350 mm	B 800 mm	H 1400 mm
Vekt	:	850 kg		
Løfting/Transport	:	Ramme med trucklommer og løfteskrev.		
Ref. sert./Ser. nr.	:	2077		

Tankvolum	:	400 l		
Q maks. 60 Hz	:	21 l/min.		
Q maks. 50 Hz	:	17 l/min.		
P maks. 60 Hz	:	280 bar		
P maks. 50 Hz	:	280 bar		
Maks. vann temperatur	:	65° C		
Tilkopling inn	:	1" Offshore klokopling		
Anbefalt forankoplet sikring	:	63 A		
Spenningsområde	:	400-690 V	50-60 Hz	

Pumpe	:	Udor GKC 21/35C stempelpumpe Ser.nr. 2001/159/01442			
Motor	:	Teve Varnost 4KTC 160M-4 Eexde IIC T4. IP-56 Ser. nr. 1350			
		380-415 VD	22,7 A	50 Hz	11,0 Kw
		660-720 VY	13,1 A	50 Hz	11,0 Kw
		380-415 VD	21,6 A	60 Hz	11,0 Kw
		440-480 VD	21,7 A	60 Hz	12,6 Kw
		660-690 VY	12,4 A	60 Hz	11,0 Kw
Filter på sugeside (fra tank)	:	1 stk. vaskbar strainer, 60micr. Delenr.. 4012093			
Vannfilter	:	1 stk. Stavfilter PX2010			
Varmekolber	:	Backer IH-5" 150lbs 850DL			Ser./Ref.
		480 V	Hz	30 Kw	
Nivåbryter	:	Magnetrol Tuffy T35-002N-B03 Eexd IIC T6 220 V			
		Ser. nr. 58537-01-001			
Startskap	:	Ceag Eexde IIC T6			Ser. nr. J2 0957/D/S
		400-690 V	50-60 Hz	Maks. last: 58 A	
Andre opplysninger	:	Leverert med 25 meter 3/8" slange og spylelanse, mannlokk i tank, flottør, nivåvakt			
Bygge år	:	2003			