



TEST PLUG GRIPTIGHT ELBOW 2" SCH 80

Dimensions

Equipment Weight - (kg).....: 2
Lifting/ Transportation.....: Transportation on pallet

Construction year

Built.....: 2019

Type

Item type.....: Testplug for Elbow / Bend
Fabricator.....: Curtiss Wright
Model.....: GTLBO-2P80
Serial no.....: 02309094-009

Flow / Pressure / Volume

P-max (bar).....: 231 P-max (PSI).....: 3350
Nominal Pipe Size (Inches).....: 2.00
Nominal Pipe Schedule.....: 80 / XS
Plug Outside Ø (mm).....: 46.0
Range of use - Minimum (Ø mm).....: 48.5
Range of use - Max recom.(Ø mm): 50.5
Plug Length (mm).....: 152

Additional information

Equipment / Functions.....: Installation:
Normal Installation Torque : 102 Nm
Maximum Installation Torque : 163 Nm

Eliminate welding on end caps/pups with GripTight Elbow Plug. Designed for testing piping, spools and pipe systems terminating in long radius elbows.

Features

- Orientation Free Installation - no need to align with elbow
- Patented Dual-Serrated GripTight MAX® gripper design
- Patented Floating, Self-Aligning grippers & seal
- Easy Installation - No welding or hot work required
- Ideal for horizontal & vertical applications
- Fits any long radius elbows
- Self-gripping design uses test pressure to increase holding power
- Saves significant time vs. welded-on end cap/pup procedures