

**I-K-M**

IKM Testing AS

Unit Nr. PP-22

PUMPE FOR PIGGING/ KJEMISK RENGJØRING



Onshore

Ramme iht. Maskindirektivet 522

Dimensjon	:	L 2000 mm	B 1400 mm	H 1620 mm
Vekt	:	1200 kg		
Løfting/Transport	:	Ramme med trucklommer		
Ref. sert./Ser. nr. ramme	:	SLFP-4-15-1300		

Q maks.	:	1300 l/min.		
P maks.	:	15 bar		
Tilkopling inn	:	1 stk	4"150# RF	
Tilkopling ut	:	1 stk	2" Camlock Male (montert i 2" 150# RF)	
Anbefalt forankoplet sikring	:	125 A		
Spenningsområde	:	380-415 VD 50 Hz / 440 VD 60 Hz		

Pumpe	:	Robuschi Keminor R50-315	Ser. nr.	9120496
Motor	:	ATB DE250M	Ser. nr.	XP111147-01
		380 VD	100 A	50 Hz
		440 VD	101 A	60 Hz
Startskap	:	Industrial		
		400-440 V	Max. load 100 A	50-60 Hz
Utstyr/Funksjoner	:			
Andre opplysninger	:	Hele pumpen er i syrefast materiale.		
Bygge år	:	1992		