



ZERION FVS
CORROSION INHIBITOR

**CORROSION
PROTECTION**

This versatile corrosion inhibiting product is widely used in applications where there are vapor spaces requiring the use of Vapor Corrosion Inhibitor (VCI) and also the possibility of water ingress that requires a strong Soluble Corrosion Inhibitor (SCI) to neutralize contaminants. Some of these applications include the following: above-ground storage tank (AST) soil side bottoms (SSB), long term preservation/mothballing of offshore structures, hydrostatic testing of complex vessels or systems, protection of voids and enclosures.

Recommended Product Applications & Guidelines

Aboveground Storage Tank Soil Side Bottoms

Zerion FVS has been used in multiple tank soil side bottom installations. It provides superior protection to exposed steel in vapor spaces and crevices under the tank bottoms and in situations when there is ingress of water into the tank foundation space. FVS can be diluted with water and injected into sand/soil base or introduced as a powder during tank construction or bottom plate refurbishment. Even for tanks with concrete pad foundations, FVS in slurry form can be introduced into the spaces between the plates and the concrete to provide corrosion protection. Zerust has also pioneered a VCI Ring system using FVS if there is no liquid injection. This VCI Ring system is recommended for all SSB installations.

Protection of Voids / Enclosures

Zerion FVS VCI chemistry actively protects exposed steel from corrosion in large volume voids and enclosures. There are multiple delivery mechanisms and product packages that can be adapted to the geometry of the structure being protected. When it is possible for the void to be hermetically sealed, a one-time introduction of FVS can provide protection for up to 2 years.

Hydrostatic Testing

Add Zerion FVS to hydrostatic testing water to provide excellent protection to exposed steel surfaces. In addition to the SCI protection, the VCI evolves to protect any air pockets or hidden voids. FVS is versatile and compatible with a variety of water profiles and works best with DI, RO or potable water with less than 150 ppm of chlorine.



Product Description

Zerion FVS is a versatile new corrosion inhibitor specifically designed to protect ferrous metals in aggressive corrosion environments where there is the possibility of the accumulation of water, moisture and/or water ingress.

Zerion FVS provides unique dual action corrosion protection making it the best in class in the market today.

Vapor Corrosion Inhibitors (VCIs) to protect the interiors of “air space” voids and exposed metal surfaces on welded joints, in crevices, at coating holidays, etc. Soluble Corrosion Inhibitors (SCIs) that mitigate corrosion from moisture accumulation or the ingress of water.

This combination penetrates gaps and interstices inside of enclosed voids to provide comprehensive coverage.

Physical Properties

Category	Details
Finish	N/A
Color	Clear Solution
Reduction	See specific application data
Temperature Range	At injection: 35°-110°F Service Temp.*: 10°-140°F *Take appropriate pressure relief measures.
Shelf Life	36 months, unopened

Availability

Product Name	Availability Description	Application Guide
Zerion FVS-S2	FVS in mesh packet	Place in center of void and seal tightly. Provides approximately 2-3m ³ volume* of protection.
Zerion FVS-S10	Mesh Sleeve 1 m (3ft.) long x 20 mm (0.75 in) diameter	Place in center of void and seal tightly. Provides approximately 3.1m ³ volume* of protection.
Zerion FVS-S15	Mesh Sleeve 1.5 m (5ft.) long x 20 mm (0.75 in) diameter	Designed for use with Inhibitor Delivery System solutions. Contact your sales representative for details.
Zerion FVS-B15	Bulk powder in pails 15 kg/pail	Dilute with water** to use as slurry. Mixing ration of 0.5% to 15% (w/v) depending on application.
Zerion FVS0B165	Bulk powder in drums 165 kg/drum	
Zerion PGH Gel 300	Swellable polymer. Bulk powder in pails.	Fills annular space of pipe casing.
Zerion PGH Gel 400	Swellable polymer. Bulk powder in pails.	Fills annular space of pipe casing. Larger granular size and increased swell time than PGH 300.



Product Storage

Keep only in original container. Store in a dry place. Store at room temperature. Store in a well ventilated place. Keep container tightly closed.

Part No. Zerion FVS-B15 3375-F-00001 Pail
Zerion FVS-B15 375-F-00001DR Drum
Zerion FVS-B15 375-F-00001TT Tote