

**I-K-M**

IKM Testing AS

Unit Nr. FU-18

OLJEFLUSHEUNIT

Offshore
Eexde IIB T4 Sone 1
Iht. Norsok Z-015



Dimensjon	:	L 1600 mm	B 800 mm	H 1800 mm
Vekt	:	580 kg tørr		
Løfting/Transport	:	Ramme med trucklommer.		
Ref. sert. ramme	:			

Tankvolum	:	210 l		
Q maks. 60 Hz	:	45 l/min.		
Q maks. 50 Hz	:	36 l/min.		
P maks.	:	210 bar		
Flowrate Q @ P 50 Hz	:	12l/min @ 210Bar	28l/min @ 100Bar	33l/min @ 50Bar
Viskositetsområde	:	13 - 68 cst. 220 cst. ved oppstart.		
Tilkopling inn	:	½" BSP male		
Tilkopling ut	:	½" BSP male		
Anbefalt forankoplet sikring	:	63 A		
Spenningsområde	:	400-690 V	50-60 Hz	

Pumpe	:	Eaton Vickers PVQ 20 - B2R SE1S 21C 21V 11P 13			
Motor	:	Teve Varnost 4KTC 132 S-04 Eexde IIB T4 Ser. nr. 1155			
		380-415 VD	10,9 A	50 Hz	5,5 Kw
		660-720 VY	6,3 A	50 Hz	5,5 Kw
		400 VD		60 Hz	5,5 Kw
		440-480 VD	11,1 A	60 Hz	6,3 Kw
		660-690 VY	5,6 A	60 Hz	5,5 Kw
Startskap	:	Technor DOL Eexde IIC T5		Ser. nr. 20884-1	
		400-690 V	50-60 Hz	Maks: last 40 A	
Filterhus tur	:	1 ea. 70T210QBPKG201			
Filterhus retur	:	1 ea. 45M210QBPKG201			
Filterhuselement tur	:	1 ea. 938777, P167842			
Filterhuselement retur	:	1 ea. 938777, P167842			
Utstyr/Funksjoner	:	Flowindikator, varmeveksler, uttak for prøvetaking, termometer			
Andre opplysninger	:	Egner seg for flushing av tubing.			
Bygge år	:	1988			