

**IKM**

IKM Testing AS

Unit Nr. FU-62

OLJEFLUSHEUNIT

Offshore Sone 1
Iht. Norsok Z-015, ATEX



Dimensjon	:	L 1500 mm	B 1100 mm	H 1410 mm
Vekt	:	1350 Kg		
Løfting/Transport	:	Trucklommer, har hjul		
Ref. ser. ramme	:	FU-62		

Tankvolum	:	300 liter		
P maks.	:	210 Bar		
Q maks.	:	95 l/min		
Flowrate Q@P (50Hz)	:	60 l/min @ 210 Bar	95 l/min @ 150 Bar	95 l/min @ 100 Bar
Viskositetsområde	:	12 - 100 cst., anbefalt 16 - 46 cst. Maks. temp. 55°C.		
Tilkopling inn	:	1" BSP Male		
Tilkopling ut	:	1" BSP Male		
Anbefalt forankoplet sikring	:	660-690V: 63 A 400-480V: 63A "treg" sikring (D-karakteristikk, uttak for motorstarter, effektbryter)		
Spenningsområde	:	400-440-480-660-690 VAC 50/60 Hz		

Pumpe	:	Moog RKP-II Radial Piston Pump HKR18 D954K224710RKP063KC21S2 Y00	Ser. Nr:		
Motor	:	II --/2 GD IIA	Sert. Nr:	BVS06ATEXHB052	
	:	ATB BD200L-4	Ser. Nr:	491717001	
	:	EEx de IIB T4	Sert. Nr:	PTB99 ATEX 1091	
	:	400 VD	IP 56	30 kW	53 A
	:	690 VY	50 Hz	30 kW	31 A
	:	400 VD	60 Hz	30 kW	52 A
	:	440-480 VD	60 Hz	34,5 kW	55-51 A
Startskap	:	660-690 VY	60 Hz	30 kW	32-30 A
	:	GHG 6645	Ser. Nr:	09-003	
	:	EEx de IIC T6	PTB 98 ATEX 1054U	NEMKO Nr:	09ATEX2074
Filterhus retur	:	Parker FF1146.Q010.BS35.GT20	40 Bar MWP		
Filter-element retur	:	FC7006.Q010.BK / D141G03A			
Filterhus trykk	:	FF7006.Q010.BS35.GT20	400 Bar MWP		
Filter-element trykk	:	FC7006.Q010.BK / D141G03A			
Utstyr/Funksjoner	:	Varmeveksler, Flowindicator, trykkregulator, manometer, nivåglass, nivåvakt, termometer, pustefilter på tank, mannlokk			
Bygge år	:	2009			