

Unit no. VIP-81



VIDEOINSPEKSJON PROBE

Dimensions

Length(mm).....: 420 Width(mm).....: 230 Height(mm).....: 80
Weight (kg).....: 1

Construction year

Built.....: 2024

Area of use / certification

Standard.....: Non EX/Atex
IP67

Type

Item type.....: Video inpeksjons probe
Fabricator.....: Teslong
Model.....: TD500

Flow / Pressure / Volume

Camera diametre (mm).....: 6.5
Range of use - Length (m).....: 1.5
Waterproof.....: No

Power supply

El.Power1.....: USB 3.0 Type C (Hz).....: (kW).....:
Battery.....: 3.7V/3000mAh Lithium Polymer Battery

Additional information

Equipment / Functions.....: Camera
1 ea. USB-C Cable
1 ea. Carrying Case
1 ea. User Manual
1 ea. max 23 GB memory cards
1 ea. Card Reader. SD / MicroSD USB 2.0, USB C, and microUSB

Monitor:
Screen 5-inch IPS LCD Screen
Screen Resolution: 854x480 pixels
Image Capturing Resolution: 640x480, 1280x720, and 1920x1080 pixels
Storage: 32GB Micro SD card
Port: Charging Port
Power Source: 3000mAh Lithium Polymer Battery
Battery Life: 3-4 hours

Camera:
Type: 2-Way 210° Articulation Probe
Diameter: 0.25 in (6.5 mm)
Probe Length: 5.08 ft (1.55-meter)
Probe Stiffness: Stiff but flexible
Megapixel: 1.0 MP
Viewing Angle: 210°
Depth of Field:
Straight-viewing Camera: 0.60 in to 3.94 in (15 mm to 100 mm)
Side-viewing Camera: 0.79 in to 1.97 in (20 mm to 50 mm)
LED Light: 6 Bright LED lights
Splash, Water, and Dust Resistant: Rated IP67
(maximum depth of 1 meter up to 30 minutes) under IEC standard 60529