



IKM Testing AS

Unit Nr. DP-19

PUMPE FOR LENSING



Dimensjon	: L: 570 mm	B: 450 mm	H: 970 mm
Vekt	: 155 kg		
Løfting/Transport	: Montert I DNV ramme med løfteskrev		

Q maks.	: 2x 2400 l/min		
P maks.	: 7 bar		
Temperatur maks.	: 40°C		
Flowrate Q@P (50Hz)	: 2x 333 l/min @ 7 Bar	2x 1400 l/min @ 5 Bar	2x 2300 l/min @ 2 Bar
Tilkopling inn	: Suction through pump casing.		
Tilkopling ut	: 6" 150# RF eller 4" 150# RF		
Spenningsområde	: 380-415V		

Pumpe	: 2stk ABS J205 HD med soft start	Ser. Nr.	
	380-415 V	43 A	50 Hz
Material	: Impeller : Cast Iron		
	Casing : Aluminium		
	Strainer : Stainless steel		
Annen informasjon	: Denne unit inneholder to stk lensepumper som er montert i en DNV godkjent subsea løfteramme med slings.		
	Begge pumpene er koplet sammen i en 6" header manifold som inneholder dobbel wafer nr.v.		
	Header manifolden har fleksible rør.		
Bygge år	: 2009		

