



IKM Testing AS

Unit Nr. HJ-48

UNIT FOR HYDROJETTING



Rig safe

Dimensjon	:	L 3550 mm	B 1500 mm	H 2500 mm
Vekt	:	Ca. 8000KG		
Løfting/Transport	:	Ramme med trucklomme og løftesling		
Ref. sert. ramme	:	HJ - 48		

Volum Diesel Tank	:	360 l
Maks flow	:	60 L/min
P maks	:	600 Bar
Tilkopling inn	:	2» camlock Male
Tilkopling ut	:	¾» BSP Male

Motor	:	Perkins-Tier 3 112 hp Maks. 2200 Rpm, Nominal 1800 rpm vann kjølt, diesel motor. 112hk @ 2,200 rpm. Tachometer, Heavy-duty 12 volt batteri, startmotor og lader Chalwyn engine over-speed valve 316 L Stainless Steel Spark Arrestor Non-Spark Fan for Radiator
Starter	:	Air Start, Vane motor inertia dive
Pumpe	:	GA-25 0-BELT DRIVEN 250 HK Sylinders 3 Stempel 34.92 mm Slaglengde 88.90 Keramiske stempel
Filter	:	Filter 1- 50 micron forfilter før vanntank og boost pumpe Filter 2- Store Bag filter for og sikre mot partikler ned til 25 micron HP pumpen.
Statsjonert	:	UK

