IKM Testing AS

Unit No. HL-135A

HELIUM LEAK DETECTOR

Dimensions

Length(mm).....: 600 Width(mm)......: 485 Height(mm)....: 225
Weight (kg).....: 12
Lifting/ Transportation.: Custom made suitcase/boxes
A: L 600mm - W 485mm - H 225mm - (12 kg)
B: L 460 mm - W 370mm - H 114mm - (2,6 kg)

Construction year

Built.....: 2012

Area of use / certification

Onshore/offshore.....: Offshore
Standard.....: EN 61010-1
EN 50270
EN 61000-6-2
EN 61000-6-3

Type

Type (HL).....: Hand-Held Leak detection (N2/He)
Item type.....: Hand-held helium leak detector
Fabricator.....: Varian
Model.....: PHD-4
Serial no.....: PHD-4 (S/N: 205554)
Procal (S/N: 3316)

Technical information

Min. Detectable leak....: 5 x 10-6 mbar l/sec. He
Delay time.....: 2 second

Connections

Outlet connection.....: RS-232, headset

Power supply

Battery.....: Charger: 100-240 Vac 50/60 Hz 1 A
Battery: NI-MH GP Cells, 12V 4500 MAH

Content

Content.....: PHD-4:
2 ea Batteries,
Travel case,
Probe set,
Carrying bag,
Power cord and adapter.
Procal:
2 ea balloons,
Power cable.