IKM Testing AS

Unit No. PT-62

TANK FOR WATER / CHEMICALS

Dimensions

Length(mm).....:	1785	Width(mm)......:	1475	Height(mm)....:	1900
Weight - Tara (kg)......:	1200	Weight - Payload (kg)	0	Weight - Gross (kg)	1200

Lifting/ Transportation.: Frame with lifting chain and forklift channels
Ex approved for use in Zone 1 offshore, ATEX, In acc with DNV 2.7-1

Certificate(s) / Serial No: S155207/11 / PT-62

Construction year

Built.....: 2011

Area of use / certification

Onshore/offshore.....: Offshore

Technical information

Tank Volume (ltr).....: 1000

Connections

Inlet connection.....: 4 ea. 2" Camlock Male
Outlet connection.....: 4 ea. 2" Camlock Female

Additional information

Equipment / Functions...: Heater:
Norske Backer EH IH – 8" 550DL
II 2 G EEx ed IIC T3 Cert. No: 04 ATEX 1489

El. power:
Recommended Backup fuse : 63A
Voltage area heaters : 400-690V 50-60Hz
400V 34,7 kW 50,1 A
440V 42,0 kW 55,1 A
480V 50,0 kW 60,1 A
660V 31,5 kW 27,6 A
690V 34,4 kW 28,7 A

Starter:
FEA13394-01 (Ser. No: J11 0092/D/M)
EEx de IIC T6 (Cert. No: 11 ATEX 2078)

Level guard, level indicator, strainer on outlet Mesh 40, thermometer, man-hole

All wet part in acid-resistant material. Immersion heater is preset at 60°C