

Unit no. FP-352



FILTER HOUSE

Dimensions

| | | | | | |
|-------------------------------|--------------------------|-----------------|-----|------------------|-----|
| Length(mm).....: | 300 | Width(mm).....: | 150 | Height(mm).....: | 350 |
| Weight (kg).....: | 3 | | | | |
| Lifting/ Transportation.....: | Transportation on pallet | | | | |

Flow / Pressure / Volume

| | |
|-----------------------|------|
| Q-max (l/min).....: | 4000 |
| P-max (bar).....: | 16 |
| Max temp. (GrC).....: | 66 |

Connections

| | |
|-------------------------|---------------------------------|
| Inlet connection.....: | 1 ea. 1" Offshore claw coupling |
| Outlet connection.....: | 1 ea. 1" Offshore claw coupling |

Filter

| | |
|-----------------------------|--------------------------|
| Filter (qty).....: | 1 |
| Filter house (type).....: | Domnick Hunter AA025EBFX |
| Filter element (type).....: | Domnick 025AA |
| Filtration medium.....: | Air |

Additional information

| | |
|-----------------------------|--|
| Equipment / Functions.....: | - Filtration of air / water removal |
| | - Particle removal (inc water and oil aerosols) down to 0,01 micron. |
| | - Max remaining oil content at 21°C is 0,01 ppm |