



WATER CUTTING MACHINE

Dimensions

Area of use / certification

Onshore/offshore...... Offshore

Standard..... CE - Norsok Z015 - Atex Zone 2

Technical information

Water Supply...... 30 ltr/min @ 6 bar

Connections

Inlet connection...... Air supply (7-10 bar)

Power supply

Fuse (qty)	1	Fuse (A):	125		
El.Power1	400 V			(Hz)	50/60
El.Power2	415 V			(Hz)	50/60
El.Power3	440 V			(Hz)	50/60
El.Power4	480 V			(Hz)	50/60
EI.Power5	690 V			(Hz):	50/60

Additional information

Equipment / Functions...... OPERATION PAREMETER WITH 0,6mm NOZZLE:

- Pressure: 1200 bar
- Water flow: 7,5 ltr/min
- Hydraulic power at Nozzle: 15 kWCutting time with one filling: 100 min

OPERATION PAREMETER WITH 1.0mm NOZZLE:

- Pressure: 1200 bar
- Water flow: 21 ltr/min
- Hydraulic power at Nozzle: 42 kW
- Cutting time with one filling: 40 min

ABRASIVE:

- Type: Garnet 0.15 0.30
- Concentration: 10 mass%
- A rugged performer fitted within a 10 Feet container, for easy mobilization.
- Remote controlled and highly efficient, giving improved work environment and potential cost and time savings.
- Extreme cutting power combined with fast cuts and precision.
- Linear rails available in both stiff, and flexible variations.

CAN BE DELIVERED WITH:

- Pipe cutting accessories
- Hole cutting accessories
- Linear/flexi rail accessories
- Hydrojetting accessories / lance

Page: 1 of 1