



EX APPROVED STARTER

Dimensions

Length(mm).....: 1660 Width(mm).....: 850 Height(mm).....: 1660
Weight (kg).....: 550
Lifting/ Transportation.....: Mounted in frame with forkliftchannels

Construction year

Built.....: 2018

Area of use / certification

Onshore/offshore.....: Offshore
Standard.....: EEx de

Power supply

Outlet no. of Engines (Qty).....: 2
El.Power1.....: 400-690VAC (Hz).....: 50/60 (kW).....:
Starter.....: GHG64 + EQ22755005 Ser.no: 23003-001 Presafe 18ATEX12783x
EX II 2(1) G Ex db [ia Ga] IIB T4 Gb Zone 1
400-440-480-660-690VAC 50-60Hz 150 A
35m H07RN-F 4G50mm2

Additional information

Equipment / Functions.....: - Soft starts with bypass contractor.
- Switch for power on, start, stop and emergency stop.
- Lamps for power on, running, PTC relay tripped and fault.
- Can be connected to and run two engines.
- Onshore: Max 170A, 45Kw@230v, 90Kw@400v, 110Kw@600v, 160Kw@690v
Due to these limitations, EX-Skap-15 cannot be used with DP-35/ DP-36 @400v/ 60Hz