



## OIL FLUSHING UNIT

### Dimensions

Length(mm).....	1600	Width(mm).....	800	Height(mm).....	1750
Weight (kg).....	400				
Lifting/ Transportation.....	Frame with forklift channels.				

### Construction year

Built.....: 1993

### Area of use / certification

Onshore/offshore.....: Offshore  
 Standard.....: Eexde IIB T4 Zone 1 In acc. to Norsok Z-015

### Flow / Pressure / Volume

Tank Volume (ltr).....	300		
Hz v Q-max measure.....	60	Q-max (l/min).....	110
Flowrate1.....	30 ltr/min @ 210 bar		
Flowrate2.....	45 ltr/min @ 500 bar		
Flowrate3.....	110 ltr/min @ 50 bar		
Min. viscosity (cst).....	10		
Max. Viscosity (cst).....	160		
Start Viscosity (cst).....	1600		

### Connections

Inlet connection.....: 1 ea 1/2" BSP  
 Outlet connection.....: 1 ea 1/2" BSP

### Pump(s)

Pump1 (type).....: Kawasaki K3VL80/B 1NRMM-PO/I-L3

### Motor / Engine(s)

Motor1 (type).....: 3KTC 160L-4  
 Motor1 (Cert. No.).....: 377

### Power supply

EI.Power1.....	380-415 VD	(Hz).....	50	(kW).....	15	(A).....	29,5
EI.Power2.....	660-720 VY	(Hz).....	50	(kW).....	15	(A).....	17
EI.Power3.....	400 V	(Hz).....	60	(kW).....	15	(A).....	29,5
EI.Power4.....	440-480 VD	(Hz).....	60	(kW).....	15	(A).....	25,5
EI.Power5.....	660-690 VY	(Hz).....	60	(kW).....	15	(A).....	16,9
Starter.....	Stahl Eexde IIC T5 Ser. No: 79896 400-690 V Max. load: 63 A, 50-60 Hz						

### Filter

Filter outlet (qty).....	1	Filterhouse (type):	Parker 24P-2	Filterelement (type):	Parker GO 1316 / D721G03A
Filter inlet (qty).....	1	Filterhouse (type):	Finnfilter FF 1290 F003 BA	Filterelement (type):	Finnfilter FC 1290 F003 BS / R727 G03P
			16 GX 20		

### Additional information

Equipment / Functions.....: Flow indicator and outlet for samples. Suitable for flushing of tubing.