



## **DIAPHRAGM PUMP**

### **Dimensions**

Length(mm).....:	520	Width(mm).....:	400	Height(mm).....:	500
Weight (kg).....:	23				
Lifting/ Transportation.....:	Mounted in Frame. Transportation on pallet				

### **Construction year**

Upgraded/rebuilt.....: 2020

### **Area of use / certification**

Onshore/offshore.....:	Offshore
Standard.....:	EX/Atex, CE, Norsok, Zone 1

### **Type**

Fabricator.....:	Depa
Model.....:	FA25 1NN (1" pump house)
Serial no.....:	788405-1

### **Technical information**

Q-max (l/min).....:	160	
P-max (bar).....:	6.8	P-max (PSI).....: 100
Flowrate1.....:	155 ltr/min @ 2 bar	
Flowrate2.....:	120 ltr/min @ 4 bar	
Flowrate3.....:	50 ltr/min @ 6 bar	
Max temp. (GrC).....:	80	

### **Connections**

Inlet connection.....:	1" Camlock Male
Outlet connection.....:	1" Camlock Female
Air connection.....:	1" offshore claw coupling
Air supply (P@Q).....:	Max 6,7 bar

### **Additional information**

Equipment / Functions.....:	Max suction, dry : 5,5 metres
	Pressure controller on air supply, for regulation of flow/pressure.
	Polypropylene pump.
	Please state liquid, for selecting seals.
	Frame and wet parts in acid-resistant material