



## DIAPHRAGM PUMP

### Dimensions

Length(mm).....: 520                                      Width(mm).....: 400                                      Height(mm).....: 500  
 Weight (kg).....: 23  
 Lifting/ Transportation.....: Mounted in Frame. Transportation on pallet

### Construction year

Upgraded/rebuilt.....: 2020

### Area of use / certification

Onshore/offshore.....: Offshore  
 Standard.....: EX/Atex, CE, Norsok, Zone 1

### Type

Fabricator.....: Depa  
 Model.....: FA25 1NN (1" pump house)

### Technical information

Q-max (l/min).....: 160  
 P-max (bar).....: 6.8                                      P-max (PSI).....: 100  
 Flowrate1.....: 155 ltr/min @ 2 bar  
 Flowrate2.....: 120 ltr/min @ 4 bar  
 Flowrate3.....: 50 ltr/min @ 6 bar  
 Max temp. (GrC).....: 80

### Connections

Inlet connection.....: 1" Camlock Male  
 Outlet connection.....: 1" Camlock Female  
 Air connection.....: 1" offshore claw coupling  
 Air supply (P@Q).....: Max 6,7 bar

### Additional information

Equipment / Functions.....: Max suction, dry : 5,5 metres

Pressure controller on air supply, for regulation of flow/pressure.  
 Polypropylene pump.  
 Please state liquid, for selecting seals.  
 Frame and wet parts in acid-resistant material