



## DIAPHRAGM PUMP

### *Dimensions*

Length(mm).....: 600                              Width(mm).....: 450                              Height(mm).....: 470  
Weight (kg).....: 30  
Lifting/ Transportation.....: Mounted in Frame. Transportation on pallet

### *Area of use / certification*

Onshore/offshore.....: Offshore  
Standard.....: Non Atex

### *Type*

Fabricator.....: Yamada  
Model.....: NDP 25 BAN  
Serial no.....: 525266

### *Flow / Pressure / Volume*

Q-max (l/min).....: 160  
P-max (bar).....: 6.8                              P-max (PSI).....: 100  
Flowrate1.....: 155 ltr/min @ 2 bar  
Flowrate2.....: 120 ltr/min @ 4 bar  
Flowrate3.....: 50 ltr/min @ 6 bar  
Max temp. (GrC).....: 80

### *Connections*

Inlet connection.....: 1" Camlock Male  
Outlet connection.....: 1" Camlock Female  
Air connection.....: 1" offshore claw coupling  
Air supply (P@Q).....: Max 6,7 bar

### *Additional information*

Equipment / Functions.....: Max suction, dry : 5,5 metres

Air regulator for regulation of flow/pressure.  
Aluminium pump/Nitril valve and diaphragm.  
Please state liquid, for selecting seals.  
Frame and wet parts in acid-resistant material