

Unit no. PF-22



## PURIFIER - OIL DRYER

### Dimensions

Length(mm).....: 800                              Width(mm).....: 700                              Height(mm).....: 1410  
Lifting/ Transportation.....: Frame with forklift channels and wheels (Ref. cert. : PF-22)

### Area of use / certification

Onshore/offshore.....: Onshore

### Type

Fabricator.....: CJC  
Model.....: PTU2 27/27 PM-EH1  
Serial no.....: 1443130101

### Flow / Pressure / Volume

Q-max (l/min).....: 1.50  
P-max (bar).....: 1  
Max temp. (GrC).....: 80

### Connections

Inlet connection.....: 1 ea. 1/2" BSP Female  
Outlet connection.....: 1 ea. 1/2" BSP Female  
Connection Drain : 1/2" BSP Male

### Pump(s)

Pump1 (type).....: PV4 14-4

### Motor / Engine(s)

Motor1 (type).....: VEM K21R 63 G 4 / 5419  
Motor1 (Cert. No.).....: 0154892080010H

### Power supply

Power (Electrical/Air).....: Electrical

### Filter

Inlet Filter.....: 1 ea. BLAT 27/27

### Additional information

Equipment / Functions.....: POWER SUPPLY MOTOR:  
- 220-240V 1,35 A 50 Hz 0,18 kW  
- 380-420V 0,77 A 50 Hz 0,18 kW  
- 255-290V 1,29 A 60 Hz 0,21 kW  
- 440-500V 0,75 A 60 Hz 0,21 kW

HEATER:  
Power Supply 3 x 400 V  
Loval Jevi, 1650 W, IP44, (Serial.no: 9906, Art.no: 23268595)

STARTER:  
C.C.Jensen (Ser. No: 01011)

- Heater, gauge, sample outlet, vent-screw
- Particle- and water-removal for mineraloils, lubricants, gearoils and dieseloils up to 150cSt.
- The filter have 3 µm filtration-capability