



## PUMP FOR PIGGING / CHEMICAL CLEANING

### Dimensions

Length(mm).....: 5150                      Width(mm).....: 2250                      Height(mm).....: 3050  
Weight (kg).....: 6750  
Lifting/ Transportation.....: Frame with forklift channels and lifting device. DNV 2.7-1  
Ref.cert. / Ser. no. frame : PP-18

### Construction year

Built.....: 2001

### Area of use / certification

Onshore/offshore.....: Onshore  
Standard.....: 100 dBA  
Power (Electrical/Diesel).....: Diesel

### Flow / Pressure / Volume

Hz v Q-max measure.....: N/A (Diesel)                      Q-max (l/min).....: 13000  
Hz v P-max measure.....: N/A (Diesel)                      P-max (bar).....: 7  
Flowrate1.....: 13000 ltr/min @ 5 bar  
Flowrate2.....: 10000 ltr/min @ 6 bar  
Flowrate3.....: 4300 ltr/min @ 7 bar

### Connections

Inlet connection.....: 10" 150# RF  
Outlet connection.....: 8" 150# RF

### Pump(s)

Pump1 (type).....: Godwin HL8 Dri Prime  
Pump1 (Cert. No.).....: S25114-2

### Motor / Engine(s)

Motor1 (type).....: Volvo TD 121 GP Approx. 260 HK at 1700 r.p.m.

### Power supply

Starter.....: Pneumatic

### Flow / Pressure / Volume

Diesel Tank Volume (ltr).....: 700  
Diesel consumption (ltr/hr).....: 60

### Additional information

Equipment / Functions.....: - Fire extinguisher 12kg.  
- Max suction height ejector 7,62 meters  
- Antistatic fan belt/fan and spark arrestor on exhaust.  
- Shut down equipment : "Shut Down" if too high rpm. at motor.