



PUMP FOR PIGGING / CHEMICAL CLEANING

Dimensions

Width(mm)..... 2410 Length(mm)...... 3170 Height(mm)...... 3000 Weight (kg)...... 12000

Construction year

Built..... 2004 Upgraded/rebuilt...... 2020

Area of use / certification

Onshore/offshore...... Offshore

Standard...... Offshore, Zone II, Norsok Z-015, ATEX

Power (Electrical/Diesel)..... Diesel

Flow / Pressure / Volume

Hz v Q-max measure...... N/A (Diesel) Q-max (I/min)..... 3000 Hz v P-max measure..... N/A (Diesel) P-max (bar)..... 46

Connections

Inlet connection...... 6" 150# RF Outlet connection...... 4" 600# RF

Pump(s)

Pump1 (type)..... Garbarino 100GHA-6

Pump1 (Cert. No.)..... 57790

Motor / Engine(s)

Motor1 (type)...... MUST BE CONNECTED TO SEPERATE MOTOR UNIT (PP-23A)

Flow / Pressure / Volume

Diesel Tank Volume (Itr)..... 1200 Diesel consumption (ltr/hr)..... 120

Additional information

Equipment / Functions...... MUST BE CONNECTED TO SEPERATE MOTOR UNIT (PP-23A), (see separate datasheets for technical

information)

Two-piece unit, where the engine and pump has to be connected via a drive shaft, hydraulic and diesel hoses

The engine has 5 step gear, but has to be locked in 4rd gear when uset with centrifugal pump. The engine is then running with 2100 rpm through a speed-up gear to 3000 rpm

Q min: 2000 l/min @ 46bar BEP: 2580 l/min @ 41bar Q maks: 3000 l/min @ 37bar