



## PUMP FOR PIGGING / CHEMICAL CLEANING

### Dimensions

Length(mm): 6724 Width(mm): 2550 Height(mm): 3124  
Weight (kg): 18500  
Lifting/ Transportation: Engide Skid Dimension: L 3912mm x W 2550mm x H 3124mm (11410 kg)  
Triplex Skid Dimension: L 2812mm x W 2550mm x H 3124mm (7090 kg)  
Frame with forklift channels and lifting slings

### Construction year

Built: 2007  
Upgraded/rebuilt: 2021

### Area of use / certification

Onshore/offshore: Offshore  
Standard: Zone II Hazardous Environment  
Power (Electrical/Diesel): Diesel

### Flow / Pressure / Volume

Hz v Q-max measure: N/A (Diesel) Q-max (l/min): 1590  
Hz v P-max measure: N/A (Diesel) P-max (bar): 758  
Flowrate1: 10 BPM (1590 ltr/min) @ 2200 Psi (152 bar)  
Flowrate2: 2 BPM (318 ltr/min) @ 11000 Psi (758 bar)

### Connections

Inlet connection: 4" 206 Thread  
Outlet connection: 3" 1502 Thread (Supplied with 3"1502 Wing x 2" 1502 Thread Crossover)

### Pump(s)

Pump1 (type): SS-600 Triplex Pump fitted with 4.5" Plungers

### Motor / Engine(s)

Motor1 (type): Detroit diesel s60, 14 liter, 600HK @ 2000RPM, Offshore spec. Atex sone 2.

### Power supply

Fuse (qty): 1 Fuse (A): 16  
El.Power1: 230V (Hz): 50/60 (kW): (A): 10-16  
Control Panel: Ceag GHG 6645 Eexde IIC T6  
230 V, 1 phase, 2,5 A, 50/60 Hz

### Flow / Pressure / Volume

Diesel Tank Volume (ltr): 700  
Diesel consumption (ltr/hr): 100

### Additional information

## Unit no. PP-32



Equipment / Functions.....: Protection: Pyroban Flame Protection Kit  
Skid Connection: Prop Shaft and ISO Locks  
Transmission: Allison 6620- Series Transmission

- Safety Shutdowns:
- 100 / Engine Overspeed
  - High Coolant Temp
  - High Exhaust Temp
  - Low Engine Oil Pressure
  - Emergency Stop
  - 110 L/Hour