

Equipment / Functions.....: PUMP ALTERNATIVE 2 (specify with order)
Kamat K-3500-A, K35036 (Serial no.: 151615/4)
Q max: 188 ltr/min
P max: 1000 bar
Connection in: 2" Fire coupling
Connection out: M36
Connection Bypass out: 1" claw coupling

PUMP ALTERNATIVE 3 (specify with order)
Kamat K-3500-A, K35065M
Q max: 613 ltr/min
P max: 300 bar
Connection in: 2" Fire coupling
Connection out: 2" BSP

PUMP ALTERNATIVE 4 (specify with order)
Conversion set for Kamat pump
Q max: 70 ltr/min
P max: 2500 bar
Connection in: 2" Fire coupling
Connection out: 9/16HP Autoclave female
Connection Bypass out: 1" claw coupling

Fixed fire extinguisher PEFS Foam.
Fire extinguisher 12kg.
- Filter feed water : Washable strainer
- Pressure gauge at pressure side
- Pressure and vacuum gauge on suction side.
- Reduction gear and air controlled clutch.
- Heater and emergency light.
- Signal to platform by: Fire, gas and common cause failure

Air/Diesel supply closes if
- To high r.p.m. on motor
- Protective guard on pump
- High exhaust temperature
- Emergency stop from control room
- High coolant temperature
- Emergency stop
- Low oil pressure
- Fire alarm
- Low air pressure
- 10% Lel Gas alarm