

Equipment / Functions.....: PUMP ALTERNATIVE 2 (specify with order)
KSB Multitec MTC, A150/04-12.1 30.63. Serial no.: 9971141794/000100/01
Q max: 6666 ltr/min
P max: 28 bar
Connection in: 8" 150# RF
Connection out: 4" 300# RF
Connection Bypass out: 1" claw coupling

PUMP ALTERNATIVE 3 (specify with order)
Kamat K-3500-A, K35065M
Q max: 613 ltr/min
P max: 300 bar
Connection in: 2" Fire coupling
Connection out: 2" BSP

PUMP ALTERNATIVE 4 (specify with order)
Conversion set for Kamat pump
Q max: 70 ltr/min
P max: 2500 bar
Connection in: 2" Fire coupling
Connection out: 9/16HP Autoclave Female
Connection Bypass out: 1" claw coupling

Fixed fire extinguisher Novec
Fire extinguisher 12kg.
- Remote control of pump (20 m).
- Filter feed water : Washable strainer
- Pressure gauge at pressure side
- Pressure and vacuum gauge on suction side.
- Reduction gear and air controlled clutch.
- Heater and emergency light.
- Signal to platform by: Fire, gas and common cause failure

Air/Diesel supply closes if
- To high r.p.m. on motor
- Protective guard on pump
- High exhaust temperature
- Emergency stop from control room
- High coolant temperature
- Emergency stop
- Low oil pressure
- Fire alarm
- Low air pressure
- 10% Lel Gas alarm