Unit no. SK2-1716-01

IKM Testing AS

HYDRAULIC TORQUE WRENCH - HYDRATIGHT SWEENEY

Dimensions

Length(mm).....: 159 Width(mm).....: 32 Height(mm).....: 119
Equipment Weight - (kg).....: 1

Type

Item type.....: Hydraulic torque wrench - HEX
Fabricator.....: Hydratight (Sweeney)
Model.....: Torque wrench RSL2, 1-7/16" (36 mm) (to be connected to Power Head 2)
Qty. available in stock.....: 4

Flow / Pressure / Volume

P-max (bar).....: 690 P-max (PSI).....: 10000
Torque min. (Nm).....: 166
Torque max. (Nm).....: 1909

Connections

Inlet connection.....: Twin hose

Additional information

Equipment / Functions.....: Dimensions (LxWxH) are for complete tool (Power Head and Square drive)

Safe
• Innovative design that completely encloses all moving parts and eliminates pinch points

Fast
• 30 – 35 degrees of operating stroke provides added productivity while avoiding “tool lock on” which is common with some torque wrench designs Versatile
• Interchangeable head design
• Power head / square drive combination for flexible use with standard impact quality sockets
• Power head / hex head combination for limited height in line solutions
• Wide range of hex sizes available for all applications
• 360 degree movement of reaction arm with simple dial lock for rapid change
• For use topside and subsea

Compact
• Designed to give optimum strength to weight and torque to weight ratios
• Minimum nose radius for trouble-free tool fit