



## HYDRAULIC TORQUE WRENCH - HYDRATIGHT SWEENEY

### Dimensions

Length(mm).....: 170	Width(mm).....: 32	Height(mm).....: 130
Equipment Weight - (kg).....: 1		

### Type

Item type.....: Hydraulic torque wrench - HEX
Fabricator.....: Hydratight (Sweeney)
Model.....: Torque wrench RSL2, 2-3/16" (55 mm) (to be connected to Power Head 2)
Qty. available in stock.....: 3

### Flow / Pressure / Volume

P-max (bar).....: 690	P-max (PSI).....: 10000
Torque min. (Nm).....: 166	
Torque max. (Nm).....: 1909	

### Connections

Inlet connection.....: Twin hose
----------------------------------

### Additional information

Equipment / Functions.....: Dimensions (LxWxH) are for complete tool (Power Head and Square drive)
--

#### Safe

- Innovative design that completely encloses all moving parts and eliminates pinch points

#### Fast

- 30 – 35 degrees of operating stroke provides added productivity while avoiding "tool lock on" which is common with some torque wrench designs
- Versatile
- Interchangeable head design
- Power head / square drive combination for flexible use with standard impact quality sockets
- Power head / hex head combination for limited height in line solutions
- Wide range of hex sizes available for all applications
- 360 degree movement of reaction arm with simple dial lock for rapid change
- For use topside and subsea

#### Compact

- Designed to give optimum strength to weight and torque to weight ratios
- Minimum nose radius for trouble-free tool fit