



HYDRAULIC TORQUE WRENCH - HYDRATIGHT SWEENEY

Dimensions

Length(mm).....:	380	Width(mm).....:	77	Height(mm).....:	296
Equipment Weight - (kg).....:	10				

Type

Item type.....:	Hydraulic torque wrench - HEX
Fabricator.....:	Hydratight (Sweeney)
Model.....:	Torque wrench RSL30, 4-5/8" (117 mm) (to be connected to Power Head 30)
Qty. available in stock.....:	6

Flow / Pressure / Volume

P-max (bar).....:	690	P-max (PSI).....:	10000
Torque min. (Nm).....:	3115		
Torque max. (Nm).....:	37965		

Connections

Inlet connection.....: Twin hose

Additional information

Equipment / Functions.....: Dimensions (LxWxH) are for complete tool (Power Head and HEX drive)

Safe

- Innovative design that completely encloses all moving parts and eliminates pinch points

Fast

- 30 – 35 degrees of operating stroke provides added productivity while avoiding "tool lock on" which is common with some torque wrench designs
- Versatile
- Interchangeable head design
- Power head / square drive combination for flexible use with standard impact quality sockets
- Power head / hex head combination for limited height in line solutions
- Wide range of hex sizes available for all applications
- 360 degree movement of reaction arm with simple dial lock for rapid change
- For use topside and subsea

Compact

- Designed to give optimum strength to weight and torque to weight ratios
- Minimum nose radius for trouble-free tool fit