



HYDRAULIC TORQUE WRENCH - HYDRATIGHT SWEENEY

Dimensions

Length(mm).....: 189	Width(mm).....: 73	Height(mm).....: 141
Equipment Weight - (kg).....: 8		

Type

Item type.....: Hydraulic Square drive torque wrench
 Fabricator.....: Hydratight (Sweeney)
 Model.....: Torque wrench RSL4 (to be connected to Power Head 4)
 Qty. available in stock.....: 4

Flow / Pressure / Volume

P-max (bar).....: 690	P-max (PSI).....: 10000
Torque min. (Nm).....: 393	
Torque max. (Nm).....: 4176	

Connections

Inlet connection.....: Twin hose

Additional information

Equipment / Functions.....: 1" Square Drive

Dimensions (LxWxH) are for complete tool (Power Head and Square drive)

Safe

- Innovative design that completely encloses all moving parts and eliminates pinch points

Fast

- 30 – 35 degrees of operating stroke provides added productivity while avoiding “tool lock on” which is common with some torque wrench designs
- Versatile
- Interchangeable head design
- Power head / square drive combination for flexible use with standard impact quality sockets
- Power head / hex head combination for limited height in line solutions
- Wide range of hex sizes available for all applications
- 360 degree movement of reaction arm with simple dial lock for rapid change
- For use topside and subsea

Compact

- Designed to give optimum strength to weight and torque to weight ratios
- Minimum nose radius for trouble-free tool fit