



VACUUM CLEANER

Dimensions

Length(mm).....: 5020 Width(mm).....: 2400 Height(mm).....: 2080
 Weight (kg).....: 4250
 Lifting/ Transportation.....: Frame with forklift channels and lifting slings. DNV 2.7-1
 Certificate(s) / Serial No:.....: FSAS/1

Construction year

Built.....: 1999

Area of use / certification

Onshore/offshore.....: Offshore
 Standard.....: Eexde IIC T4, Zone 1, Z-015

Technical information

Tank Volume (ltr).....: 3000
 Max vacuum.....: 0,05 BarA

Connections

Inlet connection.....: 1 ea. 4" Camlock Male (X-over to 2" Camlock Male is included)
 Outlet connection.....: 1 ea. 4" Camlock Male (X-over to 2" Camlock Male is included)

Pump(s)

Pump1 (type).....: Battioni Pagani WPT/480/PR
 Pump1 (Cert. No.).....: 179826

Motor / Engine(s)

Motor1 (type).....: Teve Varnost 3KTC 180M-4
 Eexde IIC T4 IP-56 PTB Nr: EX-96.D.1051
 Motor1 (Cert. No.).....: 167

Power supply

Power (Electrical/Air).....: Electrical
 Fuse (qty).....: 1 Fuse (A).....: 63
 El.Power1.....: 380-415 VD (Hz).....: 50 (kW).....: 18,5 (A).....: 35,3
 El.Power2.....: 660-720 VY (Hz).....: 50 (kW).....: 18,5 (A).....: 20,4
 El.Power3.....: 440-480 VD (Hz).....: 60 (kW).....: 21,3 (A).....: 35,2
 El.Power4.....: 660-690 VY (Hz).....: 60 (kW).....: 18,5 (A).....: 21,0
 Starter.....: Stahl DOL (Ser. No: 19297)
 Eexde IIC T5 PTB Nr: EX-91.C.1064U
 400-690 V Max load: 37 A 50-60 Hz

Additional information

Equipment / Functions.....: P max.: 1,0 BarG PSV: 1,3 Bar

 Tank and couplings are galvanize