**Unit no. VS-24B**

IKM Testing AS

# VACUUM TANK FOR VACUUM CLEANER VS-24

## *Dimensions*

| | | | | | |
|---|---|---|---|---|---|
| Length(mm)..... | 2000 | Width(mm)..... | 2000 | Height(mm)..... | 3050 |
| Weight (kg)..... | 2700 | | | | |
| Lifting/ Transportation..... | Frame with forklift channels and lifting slings. DNV 2.7-1<br>Tare 2700 Kg - Payload 5500 Kg - MGW 8200 Kg | | | | |
| Certificate(s) / Serial No:..... | 23422 / 91010-005 / VTCS-005 / VS-24B | | | | |

## *Construction year*

Built..... 2000

## *Area of use / certification*

Onshore/offshore..... Offshore

## *Technical information*

Tank Volume (ltr)..... 3000

## *Connections*

Inlet connection..... 1 ea. 4” Camlock Male for suctionhose
Other connections :
1 ea. 6” 150# RF flange
1 ea. 2” NPT Female on top of tank.

Outlet connection..... 1 ea. 4” Camlock Female for connecting to Vacuum unit
1 ea. 4” Camlock Male for emptying

## *Additional information*

Equipment / Functions..... Transitions :
- 4” female camlock to 3” male camlock
- 3” female camlock to 2” male camlock

Safetyvalve set to 0,75 Bar – used when pressure-setting tank, bleedvalve, hatch in bottum of tank for emptying and cleaning.