



Dimensions

Length(mm).....: 4572 Width(mm).....: 2438 Height(mm).....: 2438
Weight (kg).....: 11000
Lifting/ Transportation.....: Frame with forklift channels and lifting slings.
Serial Number : K100802HU

Built.....: 2010

Onshore/offshore.....	Offshore
Standard.....	86 dBA
Power (Electrical/Diesel).....	Diesel

Pump1 (type).....: MUST BE CONNECTED TO SEPERATE PUMP UNIT (PP-69B or PP-69C)

Motor1 (type).....: Detroit S60 @ 500HP
Motor1 (Cert. No.).....: 06RI037102

Control Panel.....: 12V / 95 Ah(Control, gas/fire central)

Diesel Tank Volume (ltr).....: 380
Diesel consumption (ltr/hr).....: 95

Equipment / Functions.....: HYDRAULIC POWER PACK
Hydraulic Tank Volume : 760 ltr
Q @ P max : 568 ltr/min @ 345 bar

MUST BE CONNECTED TO SEPERATE PUMP UNIT (PP-69B Triplex or PP-69C Centrifugal), (see separate datasheets for technical information)

Two-piece unit, where the engine and pump has to be connected.

The unit is remote-operated from pump control panel only, but can also be driven from local panel.

MOTOR SHUT DOWN IF:

- To high r.p.m on motor.
- Protective guard on pump.
- High exhaust temperature.
- Emergency stop from control room
- High coolant temperature.
- Emergency stop.
- Low oil pressure.
- Low air pressure.