



## PUMP FOR PIGGING / CHEMICAL CLEANING - VESSEL/SOLAS

### Dimensions

Length(mm).....: 2890                                      Width(mm).....: 1130                                      Height(mm).....: 2100  
 Weight (kg).....: 2815  
 Lifting/ Transportation.....: Frame with forklift channels and lifting devices.  
 Ref.cert. / Ser. no. frame : 1127226-1 /PP-76

### Construction year

Built.....: 2011  
 Upgraded/rebuilt.....: 2021

### Area of use / certification

Onshore/offshore.....: Offshore  
 Standard.....: 62 dBA  
 Power (Electrical/Diesel).....: Diesel

### Technical information

Hz v Q-max measure.....: N/A (Diesel)                                      Q-max (l/min).....: 8800  
 Hz v P-max measure.....: N/A (Diesel)                                      P-max (bar).....: 6

### Connections

Inlet connection.....: 6" 150# RF  
 Outlet connection.....: 6" 150# RF

### Pump(s)

Pump1 (type).....: Compressor Prime Pump QSCP150iSS (Sykes pumps)  
 CP150i Centrifugal Single Stage Compressor Prime Pump  
 Pump1 (Cert. No.).....: 1127226-1

### Motor / Engine(s)

Motor1 (type).....: Cat / Perkins 1104A-44T  
 Motor1 (Cert. No.).....: 33001327

### Technical information

Diesel Tank Volume (ltr).....: 345  
 Diesel consumption (ltr/hr).....: 11

### Additional information

Equipment / Functions.....: Max Suction: 8,2 meter  
 Solids Handling: : Sewage, thick slurries up to normal limitations of 77 mm

Pump made of 316SS, Self-priming pump, Self-suction pump, suitable hoses must be used on the suction side of the pump  
 Fire extinguisher 12kg.