Unit no. PP-77

IKM Testing AS

PUMP FOR PIGGING / CHEMICAL CLEANING - VESSEL/SOLAS

Dimensions

Length(mm).....: 2890 Width(mm).....: 1130 Height(mm).....: 2100
Weight (kg).....: 2815
Lifting/ Transportation.....: Frame with forklift channels and lifting devices.
Ref.cert. / Ser. no. frame : 1127226-1 /PP-76

Construction year

Built.....: 2011
Upgraded/rebuilt.....: 2021

Area of use / certification

Onshore/offshore.....: Offshore
Standard.....: 62 dBA
Power (Electrical/Diesel).....: Diesel

Technical information

Hz v Q-max measure.....: N/A (Diesel)
Hz v P-max measure.....: N/A (Diesel)
Q-max (l/min).....: 8800
P-max (bar).....: 6

Connections

Inlet connection.....: 6” 150# RF
Outlet connection.....: 6” 150# RF

Pump(s)

Pump1 (type).....: Compressor Prime Pump QSCP150iSS (Sykes pumps)
CP150i Centrifugal Single Stage Compressor Prime Pump
Pump1 (Cert. No.).....: 1127226-1

Motor / Engine(s)

Motor1 (type).....: Cat / Perkins 1104A-44T
Motor1 (Cert. No.).....: 33001326

Technical information

Diesel Tank Volume (ltr).....: 345
Diesel consumption (ltr/hr).....: 11

Additional information

Equipment / Functions.....: Max Suction: 8,2 meter
Solids Handling: : Sewage, thick slurries up to normal limitations of 77 mm

Pump made of 316SS, Self-priming pump, Self-suction pump, suitable hoses must be used on the suction side of the pump
Fire extinguisher 12kg.