



VIDEO INSPECTION CAMERA SYSTEM

Dimensions

Length(mm).....: 600 Width(mm).....: 500 Height(mm).....: 800
Weight (kg).....: 18
Lifting/ Transportation.....: Consist of two packages

Area of use / certification

Onshore/offshore.....: Onshore
Standard.....: CE

Type

Fabricator.....: PearPoint
Model.....: P340 USB
Serial no.....: P340 S/N: 10/RP3172-PP-0483 P342 S/N: 10/RP3175-62-PP279

Flow / Pressure / Volume

Range of use - Minimum (Ø mm)....: 36.0
Range of use - Max recom.(Ø mm): 300.0
Camera diametre (mm).....: 25.0
Range of use - Length (m).....: 60
Waterproof.....: Yes
Waterproof (bar).....: 11

Connections

Inlet connection.....: Video BNC, Phono
Outlet connection.....: Video BNC, Phono

Power supply

El.Power1.....: 100-240 V AC (Hz).....: 47/63 (kW).....: (A).....:
Battery.....: 12V DC Vehicle supply
Storage / Memory.....: 1 GB

Additional information

Equipment / Functions.....: Integrated text generator and Rod counter
Digital recording on CF-card or USB stick.

Package VIC-48A – Pelicase q/w wheels
Package VIC-48B – flexible rod q/w wheels (B 400 / L 760 / H 950 mm) (SN: 10/RP3175-62-PP-279)

25 mm camera
50 mm camera

- Contents:
- 1 ea Control unit q/w monitor, text-generator, CF-kort/USB stick.
 - 1 ea 60 m felxible rod on drum
 - 1 ea 25 mm camera
 - 1 ea 50 mm camera
 - 1 ea zentralizer
 - 1 ea feather for camera
 - 1 ea USB cable
 - 3 set Skids w/ Brushes to support camera in larger diameters
 - 1 ea power supply
 - 1 ea power supply cable
 - 1 ea 12v cable