Unit no. VIC-50A

IKM Testing AS

VIDEO INSPECTION CAMERA SYSTEM

Dimensions

Length(mm).....: 750 Width(mm).....: 550 Height(mm).....: 700
Weight (kg).....: 80
Lifting/ Transportation.....: Consist of four packages

Area of use / certification

Onshore/offshore.....: Onshore

Type

Fabricator.....: Versatrax / Spectrum

Flow / Pressure / Volume

Range of use - Minimum (Ø mm)....: 150.0
Range of use - Max recom.(Ø mm).: 1250.0
Range of use - Length (m).....: 300.0
Waterproof.....: Yes
Waterproof (bar).....: 30

Connections

Inlet connection.....: HDMI – Phono
Outlet connection.....: HDMI – Phono

Power supply

El.Power1.....: 220-240 V AC (Hz).....: 50-60 (kW).....: (A).....:

Additional information

Equipment / Functions.....: A: Rack, Control unit (L 750 mm / W 550 mm / H 700 mm - 80 Kg)
B: Pelicase, Crawler (L 1150 mm / W 650 mm / H 450 mm - 45 Kg)
C: Alu case, 300 Meters Electrical Winch (L 1120 mm / W 950 mm / H 610 mm - 211 kg)
D: Pelicase, Camera Accesories (L 470 mm / W 360 mm / H 180 mm - 7,5 kg)

Range of use:
Horisontal: 12” - 50” (300 Meters length) / Vertical: 6” - 40” (300 Meters length)
Pan 360º and tilt 280º
Delivered for either vertical or horisontal inspection.

Waterproof:
Camera waterproof until: 300 Meters (30 Bar)
Crawler waterproof until: 30 Meters (3 Bar)

Contents:
Control unit: Control panel, screen, data.
Camera: Spectrum 120HD
Crawler: Versatrax-150
300 meters cable reel
Multidirectional crawler. Adjustable.