Unit no. PP-92

IKM Testing AS

PUMP FOR PIGGING / CHEMICAL CLEANING

Dimensions

Length(mm).....: 6058 Width(mm).....: 2438 Height(mm).....: 2591
Weight (kg).....: 15000
Lifting/ Transportation.....: Frame with forklift channels and lifting devices. DNV 2.7-1 & BS12079
Ref.cert. / Ser. no. frame : M411-01-05/42

Area of use / certification

Onshore/offshore.....: Offshore
Standard.....: Offshore, Zone II, Hazardous Enviroment
Power (Electrical/Diesel).....: Diesel

Flow / Pressure / Volume

Hz v Q-max measure.....: N/A (Diesel) Q-max (l/min).....: 1600
Hz v P-max measure.....: N/A (Diesel) P-max (bar).....: 772

Connections

Inlet connection.....: 4” 206 T
Outlet connection.....: 3” 1502 T x 2” 1502 WXT

Pump(s)

Pump1 (type).....: Triplex High Performance pump HD 500 with 4 ½” plungers

Motor / Engine(s)

Motor1 (type).....: Caterpillar C18 Engine 715 BHP @ 2100 RPM

Additional information

Equipment / Functions.....: Flame Protection : Pyroban Flame Protection Kit
Transmission : Allison 6620- series Transmission