Unit no. VIC-59A

IKM Testing AS

VIDEO INSPECTION CAMERA SYSTEM

Dimensions

Length(mm).....: 480 Width(mm).....: 320 Height(mm).....: 800
Weight (kg).....: 24
Lifting/ Transportation.....: Consitst of two packages

Area of use / certification

Onshore/offshore.....: Onshore
Standard.....: CE

Type

Fabricator.....: PearPoint
Model.....: P340 USB

Flow / Pressure / Volume

Range of use - Minimum (Ø mm)....: 36.0
Range of use - Max recom.(Ø mm).: 300.0
Camera diametre (mm).....: 25.0
Range of use - Length (m).....: 120
Waterproof.....: Yes
Waterproof (bar).....: 11

Connections

Inlet connection.....: Video BNC, Phono
Outlet connection.....: Video BNC, Phono

Power supply

El.Power1.....: 100-240 V AC (Hz).....: 47/63 (kW).....: (A).....:
Battery.....: 12V DC Vehicle supply

Additional information

Equipment / Functions.....: Integrated text generator and Rod counter
Digital recording on CF-card or USB stick.

Package VIC-59A – Pelicase q/w wheels
Package VIC-59B – flexible rod q/w wheels (W 350 / L 760 / H 850 mm)

25 mm camera
50 mm camera

Contents:
1 ea Control unit q/w monitor, text-generator, CF-kort/USB stick.
1 ea 120 m flexible rod on drum
1 ea 25 mm camera
1 ea 50 mm camera
1 ea zentralizer
1 ea feather for camera
1 ea USB cable
3 set Skids w/ Brushes to support camera in larger diameters
1 ea power supply
1 ea power supply cable
1 ea 12v cable