



OIL FLUSHING UNIT

Dimensions

Length(mm).....: 1700 Width(mm).....: 950 Height(mm).....: 1550
 Weight (kg).....: 1100
 Lifting/ Transportation.....: Frame with forklift pockets and lifting lug, no slings (Ref. cert. FU-89)

Construction year

Built.....: 2013

Area of use / certification

Onshore/offshore.....: Offshore
 Standard.....:

Flow / Pressure / Volume

Tank Volume (ltr).....: 400
 Hz v Q-max measure.....: 50 Q-max (l/min).....: 26

Connections

Inlet connection.....: 1 ea 3/4" NPT Female and 3/8" MP Female
 Outlet connection.....: 1 ea 3/4" NPT Female and 3/8" MP Female

Pump(s)

Pump1 (type).....: 2 x Dynex T-104-3-PF4312/18.5Kw
 Pump2 (type).....: Maximator Air Driven Test Pump

Motor / Engine(s)

Motor1 (type).....: Koncar-MES 7AZN 180M-4T/T3

Power supply

Fuse (qty).....: 1 Fuse (A).....: 45
 El.Power1.....: 415 V (Hz).....: 50 (kW).....: (A).....: 45

Filter

Filter outlet (qty).....: 1	Filterhouse (type).: MP Filtri 3mic Pressure Filter Assy	Filterelement (type).: FHP135-1 BAG1 A03NV7
Filter inlet (qty).....: 1	Filterhouse (type).: MP Filtri 6mic Return Filter Assy	Filterelement (type).: MPF1003WG3A06WBP0 1

Additional information

Equipment / Functions.....: Flushing unit has integrated test pump:
 Q-max: 1,35 l/min
 P-max: 1034 Bar / 15000 PSI
 Air Regulator, air on/off valve, pressure vent valve, pressure isolate valve, 0-20k PSI gauge
 Directional control valve, flowmeter, PSV 5200PSI.
 Supplier Unit Name: Z2515FTR A503048