



PUMP FOR PIGGING / CHEMICAL CLEANING

Dimensions

Length(mm).....: 2140 Width(mm).....: 1360 Height(mm).....: 1315
 Weight (kg).....: 1000
 Lifting/ Transportation.....: Frame with forklift channels

Construction year

Built.....: 2014

Area of use / certification

Onshore/offshore.....: Onshore
 Power (Electrical/Diesel).....: Electrical

Flow / Pressure / Volume

Hz v Q-max measure.....: 50 Q-max (l/min).....: 3800
 Hz v P-max measure.....: 50 P-max (bar).....: 10

Connections

Inlet connection.....: 1 ea. Ø125 mm RF flange
 Outlet connection.....: 1 ea. Ø100 mm RF flange

Pump(s)

Pump1 (type).....: Euroflo, EU 100/20 MSS

Motor / Engine(s)

Motor1 (type).....: SIEMENS, 400 VD 50 Hz 55 Kw

Power supply

Fuse (qty).....: 1 Fuse (A).....: 125
 El.Power1.....: 380-415 V (Hz).....: 50 (kW).....: 55 (A).....:
 Starter.....: Star Delta Starter for 55 kW
 380-415 V 50 Hz 55 Kw
 ON / OFF switches, Outdorr IP65

Additional information

Equipment / Functions.....: Butterfly valve and manometer on the pressure side to control flow and pressure.
 Pump in acid-resistant material.