Unit no. VIC-63A

IKM Testing AS

VIDEO INSPECTION CAMERA SYSTEM

Dimensions

Length(mm).....: 600 Width(mm).....: 450 Height(mm).....: 350
Weight (kg).....: 18
Lifting/ Transportation.....: Consist of three packages

Area of use / certification

Onshore/offshore.....: Onshore

Type

Item type.....: Video tractor system
Fabricator.....: SPS
Model.....: P350 flexitrax

Flow / Pressure / Volume

Range of use - Minimum (Ø mm)....: 150.0
Range of use - Max recom.(Ø mm).: 750.0
Range of use - Length (m).....: 250
Waterproof.....: Yes
Waterproof (bar).....: 11

Connections

Inlet connection.....: BNC – composite
Outlet connection.....: BNC – composite

Power supply

El.Power1.....: 220-240 V AC (Hz).....: 50-60 (kW).....: (A).....:

Additional information

Equipment / Functions.....: A: Pelicase 1620, Control Unit /w Utilities (L 600 mm / W 450 mm / H 350 mm - 18 Kg)
B: Pelicase 1650, Tractor /W spare wheels (L 790 mm / W 470 mm / H 320 mm - 43 Kg)
C: Winch /w wheels, 250 M Electric winch (L 700 mm / W 420 mm / H 700 mm - 70 Kg)

Horizontal & Vertical / Pan 360º & tilt 280º / Multidriectional
The tractor has automatic driving/turning, see manual for further information.
It's recommended operator comes to workshop for a short briefing.

Contents:
Control Unit: Control panel - Computer – Display – Cable winch.
Camera: P350-CAM-PTZ - 10 x optical zoom
Tractor: P356 – 7 set of wheels – 2 small – 4 medium – 1 Large
250 metre Cable winch