



DIAPHRAGM PUMP

Dimensions

Length(mm).....:	650	Width(mm).....:	400	Height(mm).....:	550
Weight (kg).....:	22				
Lifting/ Transportation.....:	Mounted in Frame. Transportation on pallet				

Area of use / certification

Onshore/offshore.....:	Offshore
Standard.....:	Non Atex

Type

Fabricator.....:	Yamada
Model.....:	NDP 25 BPN
Serial no.....:	93045

Flow / Pressure / Volume

Q-max (l/min).....:	160	P-max (PSI).....:	100
P-max (bar).....:	6.8		
Flowrate1.....:	155 ltr/min @ 2 bar		
Flowrate2.....:	120 ltr/min @ 4 bar		
Flowrate3.....:	50 ltr/min @ 6 bar		
Max temp. (GrC).....:	80		

Connections

Inlet connection.....:	1" Camlock Male
Outlet connection.....:	1" Camlock Female
Air connection.....:	1" offshore claw coupling
Air supply (P@Q).....:	Max 6,7 bar

Additional information

Equipment / Functions.....:	Max suction, dry : 5,5 metres
	Pressure controller on air supply, for regulation of flow/pressure.
	Polypropylene pump.
	Please state liquid, for selecting seals.
	Frame and wet parts in acid-resistant material