



TANK FOR WATER / CHEMICALS

Dimensions

Length(mm).....: 1790 Width(mm).....: 1790 Height(mm).....: 1897
Weight - Tara (kg).....: 1200 Weight - Payload (kg)....: 0 Weight - Gross (kg).....: 1200
Lifting/ Transportation.....: Frame with lifting chain and forklift channels
Ex approved for use in Zone 1 offshore, ATEX, In acc with DNV 2.7-1
Certificate(s) / Serial No:.....: 216371.1 / PT-82

Construction year

Built.....: 2015

Area of use / certification

Onshore/offshore.....: Offshore

Flow / Pressure / Volume

Tank Volume (ltr).....: 1000

Connections

Inlet connection.....: 4 ea. 2" Camlock Male
Outlet connection.....: 4 ea. 2" Camlock Female

Additional information

Equipment / Functions.....: Heater:
Norske Backer EH IH – 8" 550DL
II 2 G Ex ed IIC T3 Gb (Cert. No: 13 ATEX 1549X)

El. power:
Recommended Backup fuse : 63A
Voltage area heaters : 400-690V 50-60Hz
400V 34,7 kW 50,1 A
440V 42,0 kW 55,1 A
480V 50,0 kW 60,1 A
660V 31,5 kW 27,6 A
690V 34,4 kW 28,7 A

Starter:
19-EC-001 (Ser. No: D1093D)
EEx demb [ia] IIB T6 (Cert. No: 15 ATEX 2016)

Level guard, level indicator, strainer on outlet Mesh 40, thermometer, man-hole

All wet part in acid-resistant material. Immersion heater is preset at 60°C