



## LINE BORING MACHINE

### Dimensions

Length(mm).....	1270	Width(mm).....	890	Height(mm).....	1070
Weight - (kg).....	575				
Lifting/ Transportation.....	Shipped in 2 containers + HPU.				

### Area of use / certification

Onshore/offshore.....	Offshore
-----------------------	----------

### Type

Description.....	Hydraulic driven line boring machine
Fabricator.....	Climax
Model.....	BB6000
Serial no.....	12000

### Flow / Pressure / Volume

Minimum bar length (mm).....	1130.3
Max bar length (mm).....	3048.0
Minimum drill hole Ø (mm).....	223.5
Max drill hole Ø (mm).....	1036.3

### Power supply

Power (Electrical/Hydraulic).....	Hydraulic
-----------------------------------	-----------

### Additional information

Equipment / Functions.....	Hydraulic supply : 37,9 l/min @ 246 bar Rotational Drive Unit 6:1 gear ratio reduction
----------------------------	---

Machine can be used for line boring, drilling, facing, conventional boring and grooving.

#### Quick and Easy Setup

- Modular components make setup quick and easy.
- Fast and easy setup using high quality cast-iron set-up cones and spherical bearing mounts.
- Patented spherical bearing mounting system allows quick setup, with up to 5° of bearing misalignment.
- Typical set-up time for an experienced operator is 30 minutes or less.