



## LINE BORING MACHINE

### Dimensions

Equipment Weight - (kg).....: 201  
Lifting/ Transportation.....: Shipped in 2 containers + HPU.

### Area of use / certification

Onshore/offshore.....: Offshore

### Type

Description.....: Hydraulic driven line boring machine  
Fabricator.....: Climax  
Model.....: BB5000  
Serial no.....: 12710

### Flow / Pressure / Volume

Minimum bar length (mm).....: 1219.2  
Max bar length (mm).....: 7315.2  
Minimum drill hole Ø (mm).....: 38.1  
Max drill hole Ø (mm).....: 609.6

### Power supply

Power (Electrical/Hydraulic).....: Hydraulic

### Additional information

Equipment / Functions.....: Machine: L 1334mm x W 686mm x H 419mm  
Bar: L 1892mm x W 165mm x H 178mm

Hydraulic supply : 37,9 l/min @ 246 bar  
Mounting Options: Single Arm, Double Arm, Universal, ID  
Rotational Drive Unit 4:1 gear ratio reduction

Machine can be used for line boring, drilling, facing, conventional boring and grooving.

#### Quick and Easy Setup

- Modular components make setup quick and easy.
- Fast and easy setup using high quality cast-iron set-up cones and spherical bearing mounts.
- Patented spherical bearing mounting system allows quick setup, with up to 5° of bearing misalignment.
- Typical set-up time for an experienced operator is 30 minutes or less.