



PIPE CUTTING MACHINE

Dimensions

Equipment Weight - (kg).....: 102
Lifting/ Transportation.....: Transportation on pallet

Area of use / certification

Onshore/offshore.....: Offshore

Type

Description.....: Cut and bevel. Low weight.
Fabricator.....: Mactech
Model.....: 824USS
Serial no.....: 9003
Mounting (ID / OD).....: External (OD)

Flow / Pressure / Volume

Range of use - Minimum (Ø mm)....: 457.2
Range of use - Max recom.(Ø mm): 609.6

Connections

Air supply (P@Q).....: 2,8 m³/min @ 6,9 bar.

Power supply

Hydraulic Supply.....: Hydraulic Drive HPU Requirement 10-15 gpm @1000 psi (38-57lpm@69 bar) continuous pressure - includes hose whips and quick connects

Additional information

Equipment / Functions.....: When used with pneumatic feed - to be used with water separator/lubricator.

Features

- Sever or simultaneous Sever / Bevel 2" to 6" Nominal Pipe.
- Cold Cutting in hazardous environments.
- Exceptionally rigid, split-frame for precise on-site machining.
- Tool Holder accepts standard 3/4" or 1" tool bits.
- Lightweight, low clearance design for easy handling in tight workspaces.