



## MILLING MACHINE

### Dimensions

Length(mm).....: 2200                                  Width(mm).....: 560                                  Height(mm).....: 470  
 Weight (kg).....: 400

### Area of use / certification

Onshore/offshore.....: Offshore

### Type

Description.....: Portable mill  
 Fabricator.....: Climax  
 Model.....: PM3000  
 Serial no.....: 9131

### Specifications

Power Options.....: Air  
 Max X-Axis Travel (mm).....: 1244.6  
 Max Y-Axis Travel (mm).....: 203.0  
 Max Vertical Travel.....: 76.0  
 Spindle size.....: 0,75" (20mm)

### Additional information

Equipment / Functions.....: Climax's PM Series 3-axis portable milling machines provide precise and versatile on-the-job milling capabilities. They are designed to be attached either to the work piece or to a fabricated frame beside it. Downtime savings will pay for the machine in a short time.

- All gears and drives are permanently lubricated and sealed to allow operation in any position.
- Precision machined dovetail ways and adjustable gibs provide smooth accurate travel
- The vertical adjusting screw is calibrated for accurate adjustments and has a locking nut for zeroing.
- Power is delivered by a triple gear reduction power head with in-line electronic speed control providing spindle speeds from 280 to 525 rpm.
- Spindle accepts standard 3/4" Weldon-type shank cutting tools. A 20 mm spindle is available for metric applications