



## AIR DRIVEN SAW - CLAMP MOUNTED

### Dimensions

Length(mm).....: 400                                      Width(mm).....: 41                                      Height(mm).....: 135  
Equipment Weight - (kg).....: 3  
Lifting/ Transportation.....: Transportation on pallet

### Area of use / certification

Onshore/offshore.....: Offshore  
Standard.....: Machinery Directive 2006/42/EC  
ATEX Directive 94/ 9/EC  
ATEX CE II 2G T5 X

### Type

Description.....: Air driven saw - Chain/clamp mounted  
Fabricator.....: Cengar  
Model.....: CL75  
Serial no.....: 12507

### Flow / Pressure / Volume

Speed (stroke/min).....: 1200  
Stroke length (mm).....: 45

### Connections

Air connection.....: Please specify with order (Claw, hansen, osv)  
Air supply (P@Q).....: 5-6 bar (max 6 bar)  
Air consumption : 0,168 m3/min

### Additional information

Equipment / Functions.....: Must be used with water-separator and oil-lubricator.

#### BLADES:

- Blade must be ordered separately.
- CL75: 19mm (3/4") wide Bi-Metal blad

#### Blades types:

- Saw Blade for Hack-Saw 14 tpi (Stock No.: FOHACK0003)
- Saw Blade for Hack-Saw 18 tpi (Stock No.: FOHACK0005)
- Saw Blade for Hack-Saw 24 tpi (Stock No.: FOHACK0010)
- Saw Blade 305x19x0,9mm 10-14TPI, BLU (Stock No.: 9586210)
- Saw Blade 204x19x0,9mm 18TPI, BLU (Stock No.: 9586211)

- Vibration Level averaged 3,2 m/s<sup>2</sup>
- Sound Pressure Level 82.9 db.
- Sound Power Level 92.4 db.